

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Information

MANUFACTURER: CERAM-KOTE COATINGS INCORPORATED
(Formerly Freecom, Inc.)
1800 Industrial Drive
Big Spring, Texas 79720

TELEPHONE: For information purposes 8:00 a.m. to 5:00 p.m. CDT
(432) 263-8497 (800) 346-4299

EMERGENCY: For Chemical Emergency
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)



DATE OF PREPARATION: December 12, 2011

SUPERSEDES MSDS DATED: August 1, 2011

PRODUCT NAME: CeRam-Kote SPG

Section 2. Composition and Ingredient Information

| Common Name | Chemical Name | CAS Number | Weight % |
|---|-------------------------------------|-------------------------|----------|
| PART-A CeRam-Kote SPG (Base) | | | |
| Ceramic Filler | Ceramic Filler | 14807-96-6 1344-28-1 | 50 - 60 |
| *Proprietary #1 | Epoxy Resin | 28064-14-4 | 30 - 40 |
| PART-B CeRam-Kote SPG (Curing Agent) | | | |
| Modified Aliphatic Polyamine | *Trade Secret | N/A | 2 to 3** |
| Diethylenetriamine Mixture | N-(2-Aminoethyl)-1,2-Ethanediamine | 111-40-0 | 2 to 3** |
| Bisphenol A | 4,4'-(1-Methylethylidene) Bisphenol | 80-05-7 | 2 to 3** |

*The specific chemical identity of this ingredient is declared proprietary information under 29 CFR 1910.1200, section (i) Trade Secret. Hazard information is provided in this MSDS for this ingredient.

**This percentage is from a fully catalyzed mix. The ratio is 7 parts A (Base) to 1 part B (Curing Agent). This ratio is from a catalyzed mix of CeRam-Kote SPG.

Section 3. Physical Data

| Description | CeRam-Kote SPG (Catalyzed) | PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|--|----------------------------|-------------------------------|---------------------------------------|
| Boiling Point | N/A | N/A | > 392°F (200°C) |
| Vapor Density (Air = 1) | >Air | >Air | >Air |
| Solubility in Water | Insoluble | Insoluble | Miscible |
| Viscosity (centapoise) | >200,000 | >200,000 | 3,000 to 5,000 |
| pH | Slightly Alkaline | Slightly Acidic | Alkaline |
| Appearance and odor | Paste, aromatic odor | Paste, aromatic odor | Translucent, amine odor |
| Percent Solids by Volume | 100.0 | 100.0 | 100.0 |
| Density – packaged (on average) | 1.61 | 1.68 | 1.07 |
| Percent Volatiles by weight | 0.0 | 0.0 | 0.0 |
| Non-Volatiles | 100.0 | 100.0 | 100.0 |

Section 4. Fire Fighting Measures

| Description | CeRam-Kote SPG (catalyzed) and/or PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|---|---|--|
| Flashpoint | Greater than 200°F (93.3°C) | > 200°F (93.3°C) |
| Auto Ignition Temperature | No data | N/A |
| Extinguishing Media | Water fog, CO ₂ , or dry chemical | Foam, CO ₂ , or dry chemical. A water spray can also be used. |
| Unusual Fire and Explosion Hazards | No special fire hazards are known to be associated with this product. | Decomposition and combustion products may be toxic. |
| Fire Fighting Instructions | Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS. | Use self contained breathing apparatus. |
| Hazardous Combustion Products | May form: Carbon dioxide and carbon monoxide, various hydrocarbons. | Carbon monoxide, carbon dioxide, aldehydes, and nitrogen oxides. |

Section 5. Reactivity Data

| Description | CeRam-Kote SPG (catalyzed) and/or PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|---|--|--|
| Stability | Stable | Stable |
| Incompatibility | Strong oxidizing agents | Avoid strong oxidizing agents, acids, copper and its alloys. |
| Hazardous Decomposition Products | May form: carbon dioxide and carbon monoxide, and aldehydes. | Carbon monoxide, carbon dioxide, aldehydes, and nitrogen oxides. |
| Hazardous Polymerization | Product will not undergo hazardous polymerization. | Will not occur. |

Section 6. First Aid Measures

| Description | CeRam-Kote SPG (catalyzed) and/or PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|-------------------|--|--|
| Inhalation | If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult. | Remove to fresh air. Give oxygen if breathing is difficult. |
| Eyes | Flush with running water for at least 15 minutes. Seek medical attention. | Immediately flush eyes with water for at least 15 minutes. Get immediate medical assistance. |
| Skin | Wash with flowing water. Remove contaminated clothing and launder before re-wearing. If irritation persists, seek medical attention. | Promptly wash thoroughly with mild soap and water. |
| Ingestion | DO NOT induce vomiting. Seek medical attention. | DO NOT induce vomiting. Seek medical attention. |

Section 7. Health and Safety

| | CeRam-Kote SPG (catalyzed) and/or PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|--|---|---|
| Primary Routes of Exposure | Inhalation, skin, eye | Dermal |
| Potential Health Effects | <p>Eye: Exposure may cause mild eye irritation. Symptoms may include stinging, tearing, and redness.</p> <p>Skin: Exposure causes skin irritation. Symptoms may include: allergic skin reaction.</p> <p>Swallowing: Single does oral toxicity is low. Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful</p> <p>Inhalation: Exposure to vapor or mist is possible.</p> <p>Target Organ Effects: Overexposure to this material has been suggested as a cause of the following effects in humans, and may aggravate pre-existing disorders of these organs: skin sensitization.</p> | <p>Overexposure effects: Direct or prolonged skin or eye contact can cause skin and eye burns.</p> <p>Swallowing liquid can burn mouth and cause nausea, vomiting, diarrhea, abdominal pain and collapse. Can cause allergic skin and respiratory reactions after repetitive exposure. Animal studies on component(s) have shown effects on liver and fetus.</p> |
| Medical Conditions Aggravated by Exposure | Persons with a history of chronic respiratory disease, skin disease, or central nervous system disorders may be at increase risk for worsening their conditions from exposure to this product. | Persons with a history of allergic conditions may be at increased risk for worsening their conditions from exposure to this product. |
| Symptoms of Exposure | Gastrointestinal irritation (nausea, vomiting, diarrhea), irritation (nose, throat, respiratory tract). | Gastrointestinal irritation (nausea, vomiting, diarrhea), irritation (nose, throat, respiratory tract). |

Section 8. Exposure Controls and Personal Protection

| INGREDIENT | OSHA PEL (8-HR TWA) | ACGIH TLV (8-HR TWA) |
|-------------------------------------|--|------------------------|
| *Proprietary #1 | Not established | Not established |
| Ceramic Filler | 2 mg/m ³ | 2 mg/m ³ |
| Modified Aliphatic Polyamine | None established | None established |
| Diethylenetriamine Mixture | 1 PPM | 1 PPM (skin) |
| Bisphenol A | 5 mg / m ³ (respirable fraction) 15 mg / m ³ (total fraction) | 10 mg / m ³ |

Section 9. Regulatory Information

| Description | PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|-----------------------|--------------------------------------|--|
| TSCA Status | Each ingredient is on the inventory | Chemical components listed on inventory |
| SARA Title III | Sec 302: None Sec 313: None | Sec 313: 4,4'-Isopropylidenediphenol |

Section 10. Engineering Controls and Personal Protection

| Description | CeRam-Kote SPG (catalyzed) and/or PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|-------------------------------|--|--|
| Engineering Controls | General dilution ventilation and/or exhaust ventilation should be provided as necessary to maintain exposures below regulatory limits. | Good general mechanical ventilation is recommended. Local exhaust recommended. |
| Respiratory Protection | If irritation occurs, or if the TLV or PEL is exceeded, use a NIOSH/MSHA approved air purifying respirator with organic vapor cartridges or canisters, or supplied air respirators. Use respiratory protection in accordance with your company's respiratory program, local regulations or OSHA regulations under 29 CFR 1910.134. | Organic chemical cartridge respirator, if needed. |
| Dermal Protection | Loose fitting long sleeved shirt, long pants and chemical resistant gloves such as neoprene or natural rubber gloves. | Wear impervious rubber gloves. |
| Eye Protection | Chemical protective goggles. | Splash-proof chemical goggles. |

Section 11. Spills, Leaks and Disposal

| Description | CeRam-Kote SPG (catalyzed) and/or PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|--------------------------------|--|--|
| Land Spill | Small Spill: Absorb paste on vermiculite, floor absorbent or other absorbent material. Large Spill: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. | Avoid all personal contact. Take up with absorbent material. Shovel into closeable containers. Flush contaminated area with water. |
| Water Spill | No data | This product is miscible in water. That means it is totally dissolved when mixed with water. Due to this property, this is considered a marine pollutant; however, when mixed with part A, and after the product cures, it is totally inert. |
| Air Release | No data | This product reacts with air by absorbing the moisture out of the air. Take up with absorbent material. Shovel into closeable containers. Flush contaminated area with water. |
| Disposal Considerations | Dispose of in accordance with all applicable local, state, and federal regulations. | Not a hazardous waste under RCRA (40 CFR 261). |

Section 12. Transport Information

| Description | PART-A: CeRam-Kote SPG (Base) | PART-B: CeRam-Kote SPG (Curing Agent) |
|---------------------------------------|-------------------------------|---|
| DOT/IATA/IMDG Shipping Names | Not regulated | Amines, Liquid, Corrosive, N.O.S., (Diethylenetriamine Mixture) |
| Hazard Class or Division | N/A | 8 |
| Secondary | None | None |
| UN Identification Number | N/A | UN 2735 |
| Packing Group | N/A | III |
| Label(s) required | N/A | Corrosive (8) |
| Quantity Limitations(Air only) | | |
| Passenger Aircraft | N/A | 5 liter (5 quarts) |
| Cargo Aircraft | N/A | 60 liters (15 gallons) |
| Packing Instructions | | |
| Passenger Aircraft | N/A | 852 |
| Cargo Aircraft | N/A | 856 |