

# MATERIAL SAFETY DATA SHEET

## Section 1. Product and Company Information

**MANUFACTURER:** CERAM-KOTE COATINGS, INCORPORATED  
P.O. Box 2119  
Big Spring, Texas 79721-2119

**TELEPHONE:** For information purposes 8:00 a.m. to 5:00 p.m. CDT  
(432) 263-8497 (800) 346-4299

**EMERGENCY:** (432) 263-8497 (800) 346-4299

**DATE OF PREPARATION:** July 8, 2009

**SUPERCEDES MSDS DATED:** March 23, 2007



**PRODUCT NAME:** CeRam-Kote Thinner 3

The information contained herein is accurate to the best of our knowledge. However, Freecom, Inc does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

## Section 2. Composition and Ingredient Information

Material Description	CAS Number	Weight %
Acetone	67-44-1	N/A

### Exposure Limits

INGREDIENT	OSHA PEL (8-HR TWA)	ACGIH TLV (8-HR TWA)	OTHER LIMITS RECOMMENDED
Acetone	1000 ppm	750 ppm	STEL (OSHA/ACGIH) 1000 ppm CEILING - none known

## Section 3. Physical Data

Description	CeRam-Kote Thinner 3
Boiling Range	56-57°C / 133-135°F
Vapor Pressure (mm of Hg @ 20°C)	186.0
Nonexempt VOC Partial Pressure (mm of Hg @ 20°C)	0.0
Vapor Density (air = 1)	2.0
Water Absorption	Complete
Gravity @ 60°F: API: Specific Gravity (Water = 1) : Pounds / Gallon:	47.20.7926.597
VOCs (>0.44 lbs./sq. in.) :	100.0 Vol. % / 792.0 g/l / 6.597 lbs/gal
Total VOCs (TVOC):	100.0 Vol. % / 792.0 g/l / 6.597 lbs/gal
Nonexempt VOCs (CVOC) :	0.0 Vol. % / 0.0 g/l / 0.000 lbs/gal
Odor	Ketone
Appearance	Liquid, Water - White
Solvency Parameters: HKB (Hydrogen Bonding): PKB (Polarity) : DKB (Dispersion) :	32.4 42.0 25.6
Refractive Index	1.358

## Section 4. Fire and Explosion Hazard Data

Description	CeRam-Kote Thinner 3
Flammability Classification OSHA	Class IB
DOT Shipping Name	Acetone, 3 UN1090, PG-II
Flashpoint (Test Method):	-16°C / 2°F (TCC)
Lower Flammable Limit In Air (% by vol.)	2.6
Auto Ignition Temperature	515°C / 960°F (Lowest Component)
Extinguishing Media	NFPA Class B extinguishers (Carbon Dioxide or foam) for Class IB liquid fires
Unusual Fire and Explosion Hazards	EXTREMELY FLAMMABLE!! Vapors can cause flash fire. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electric equipment and open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!
Special Fire Fighting Procedures	Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves and rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

## Section 5. Reactivity Data

Description	CeRam-Kote Thinner 3
Stability	Stable
Materials to avoid	Isolate from strong oxidizers such as permanganates, chromates & peroxides.
Hazardous Decomposition Products	Carbon Monoxide, Carbon Dioxide from burning.
Hazardous Polymerization	Will not occur.
Conditions to avoid	Isolate from oxidizers, heat, sparks, electric equipment and open flame.

## Section 6. Ecological Information

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts >. 0.1%.

## Section 7. Toxicological Properties

Description	
This product meets requirements of Southern California AQMD Rule 443.1 and similar regulations. California Proposition 65: This product contains no known chemicals known to the State of California to cause cancer or reproductive toxicity. If >5000 pounds of this product is in one container the "RQ" is exceeded.	
Acetone	Lowest Know Lethal Dose Data Lowest Known LD50 (Oral) 5340.0 mg/kg (Rabbits)
	Lowest Known LC50 (Vapors) 21000 ppm (Cats)
	Lowest Known LD50 (Skin) 20000.0 mg/kg (Rabbits)
Threshold Limit Value:	750 ppm (Freshly Prepared)

## Section 8. Health Hazard Data

Description	CeRam-Kote Thinner 3
<b>Acute Hazards</b>	<p><b>Eye &amp; Skin Contact:</b> Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.</p> <p><b>Inhalation:</b> Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.</p> <p><b>Swallowing:</b> Swallowing can cause abdominal irritation, nausea, vomiting and diarrhea.</p> <p><b>Conditions Aggravated:</b> Persons with severe skin, liver or kidney problems should avoid use.</p>
<b>Emergency and First Aid Procedures:</b>	<p><b>Eye Contact:</b> For eyes, flush with plenty of water for 15 minutes and get medical attention.</p> <p><b>Skin Contact:</b> In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap and water. Wash contaminated clothing before reuse.</p> <p><b>Inhalation:</b> After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.</p> <p><b>Swallowing:</b> If swallowed, CALL A PHYSICIAN IMMEDIATELY! Induce vomiting promptly using physician's instructions or by having patient stick finger down throat. Never give anything by mouth to an unconscious person.</p>
<b>Carcinogenicity</b>	This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.

## Section 9. Spill or Leak Procedures

Description	CeRam-Kote Thinner 3
<b>Steps to be Taken in Case Material is Released or Spilled</b>	Stop spill at source. Dike area and contain. Clean up remainder with absorbent materials. Mop up and dispose of. Persons without proper protection should be kept from area until cleaned up.
<b>Waste Disposal Method</b>	Recycle or dispose of observing local, state and federal health, safety and pollution laws. If questions exist, contact the appropriate agencies.
<b>Other Precautions</b>	Vapors may ignite explosively and spread long distances. Prevent vapor buildup. Put out pilot lights and turn off heaters, electric equipment and other ignition sources during use and until all vapors are gone.

## Section 10. Safe Handling and Use Information

Description	CeRam-Kote Thinner 3
<b>Handling</b>	<p>Isolate from oxidizers, heat, sparks, electric equipment and open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin and eyes.</p> <p>Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse.</p> <p>Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze or weld. Empty container very hazardous! Continue all label precautions.</p>
<b>Storage</b>	<p>Vapors may ignite explosively and spread long distances. Prevent vapor buildup. Put out pilot lights and turn off heaters, electric equipment and other ignition sources during use and until all vapors are gone.</p> <p>Do not store above 49°C / 120°F. Store large amounts in structures made for OSHA Class IB liquids. Keep container tightly closed and upright when not in use to prevent leakage.</p>

## Section 11. Exposure Controls / Personal Protection

Description	CeRam-Kote Thinner 3
<b>Exposure Controls</b>	Ventilate to keep vapors of this material below 375 ppm. If over TLV, in accordance with 29 CFR 1910.134, use NIOSH approved positive-pressure, self-contained breathing apparatus. Consult Safety Equipment Supplier. Use explosion-proof equipment.
<b>Ventilation</b> Local Exhaust Mechanical (General) Special Other	Necessary Acceptable None None
<b>Personal Protections</b>	Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse.

## Section 12. General Comments

CeRam-Kote Thinner 3
The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

## Section 13. Right to Know – Section 313 – Supplier Notification

CeRam-Kote Thinner 3
All components of this product are on the TSCA list. This material contains no known products restricted under SARA Title III, Section 13 in amounts greater or equal to 1%. This MSDS complies with 29 CFR 1910.1200 (Hazard Communication Standard). This information must be included in all MSDSs that are copied and distributed for this material. Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers and users of this product.

## Section 14. Transport Information

Description	CeRam-Kote Thinner 3
<b>DOT/IATA/IMDG Shipping Names</b>	Acetone
<b>Hazard Class or Division</b>	3
<b>Secondary</b>	None
<b>UN Identification Number</b>	UN 1090
<b>Packing Group</b>	II
<b>Label(s) required</b>	Flammable (3)
<b>Quantity Limitations (Air only)</b>	
<b>Passenger Aircraft</b>	5 liters (5 quarts)
<b>Cargo Aircraft</b>	60 liters (15 gallons)
<b>Packing Instructions</b>	
<b>Passenger Aircraft</b>	305
<b>Cargo Aircraft</b>	307